



Roofnado™ AnchorDeck™

Roofnado™ AnchorDeck™ is the industry leader in synthetic roofing underlayment for sloped roofs. Trusted by professionals, Roofnado™ offers innovative underlayment solutions that provide superior walkability and ease of installation. Its high-traction walking surface ensures safety and confidence during installation, while its exceptional durability is built to withstand the toughest conditions. AnchorDeck™ is versatile and ideal for use under asphalt shingles, residential metal, and primed cedar shakes.

AnchorDeck™ meets all relevant code requirements, including ASTM D226, ASTM D4869, and AC 188 as mandated by ICC-ES. Choose AnchorDeck™ for a reliable, high-performance roofing solution that today's professionals trust.

Features & Benefits

- AnchorDeck™ has a unique coating technology which allows underlayment to be anchored to the deck prior to applying fasteners.
- Innovative high traction walking surface
- No stretching around fasteners & no blow-offs!
- All temp. All weather performance; remains flexible and easy to install in freezing or extremely hot conditions (-40° to 240° F)
- Meets ASTM D226 Types I & II and D4869 Types II & IV
- Meets the performance requirements of CAN/CSA A123.3
- Miami-Dade County Product Control Approved
- ICC-ES ESR-4055 Approved | FBC Approved – FL21895
- Class A Fire Rating - ASTM E108
- Texas Department of Insurance Approved
- 180 Days UV Exposure
- 30 year warranty
- 48" wide
- Custom dual-logo printing available

MIAMI-DADE COUNTY
APPROVED

Test/Standard*

Typical Value

Tensile Strength ASTM D5034	MD 95 lbs (43 kg) CD 85 lbs (38.5 kg)
Tear Strength ASTM D4533	MD 18 lbs (8.16 kg) CD 16 lbs (7.26 kg)
Liquid Water Transmission ASTM D4869	Pass
Fire Rating ASTM E108	Class A
UV Exposure	6 Months
Temperature Range	-40° F - 240° F



Roll/Pallet Specs

Length per roll:	250' / 76.2 m
Width per roll:	48" / 1.2 m
Weight per roll:	23 lbs / 10.4 kg
Roll size:	10 sq / 93 m ²
Rolls per pallet:	49
Weight per pallet:	1,177 lbs

*Test data is based on average taken over several production runs and should not be considered or interpreted as minimum or maximum values. Values are typical data and not limiting specifications. All values ± 10 %. This product is manufactured in accordance with national standards which allow for non-critical variances in weights and measures.

†When correctly installed as per installation instructions. All product installation instructions are available to download or view from our website.

RN AD SS JUL24

**Switch to Roofnado™
and start saving on labor,
time & money.
Contact us today!
www.sentrybuilding.com**



Sentry Building Innovations | 1209 Orange Street, Wilmington, New Castle, Delaware 19801 | Contact Customer Service: 1-843-735-1773